

Lamp Current (A): 10.3A
 Ignitor Voltage (Min.): 4KV
 Luminaire Rating: Enclosed
 Burning Position: Horizontal $\pm 15^\circ$

MBIL S 2000W

Product Number: 22132

Lamp Type: High Wattage Double Ended

Performance Data


Light Output (Lumens @ 100 hours)	215000
Lamp Lumens Per Watt	100
Rated Life (Hrs. @ 10 Hr. /Start)	6000
Correlated Colour Temperature (K)	5200
Chromaticity (CIE - X Y)	340, 360
Colour Rendering Index (CRI) or (Ra)	65
Typical Warm Up Time (Minutes)	10
Typical Hot Restart Time (Minutes)	15
Burning Position	Horizontal $\pm 15^\circ$




Physical Data / Requirements

Base Designation	Special-Contact
Bulb Designation	T25
Bulb Diameter (mm)	25
Max. Overall Length (mm)	311
Light Centre Length (mm)	N/A
Effective Arc Length (mm)	188
Max. Base Temperature (°C)	350
Max. Bulb Temperature (°C)	850
Luminaire Type	Enclosed
Socket Pulse Rating (KV)	6
Mercury Content (mg)	87.0

Lumen Maintenance



Lamp Mortality



Lamp Electrical Data / Requirements

IEC Standard	-
Lamp Wattage (W)	2150
Lamp Operating Voltage (V)	230
Lamp Operating Current (Amps)	10.3
Min. Open Circuit Voltage (RMS)	342
Min. Starting Pulse (Peak V)	4000-6000
Min. Pulse Width at 3600V (microseconds)	1.3
Min. Pulse Rate Per 1/2 cycle	1
Pulse Position (Electrical Degrees)	60-90, 240-270

Revision: 30.08.12

Notes:

1) This Product Specification contains data about typical performance at nominal power. Actual values may depend on ballast and applications. Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives.